

STEAM METHANE REFORMING (SMR) FOR HYDROGEN PRODUCTION WITH CARBON CAPTURE FROM PRESSURE SWING ADSORPTION (PSA) TAIL GAS USING METHYLDIETHANOLAMINE

Date of factsheet	27-7-2018
Author	Jacob Janssen
Sector	Hydrogen supply
ETS / Non-ETS	ETS
Type of Technology	Steam methane reforming (SMR)
Description	<p>Steam methane reforming (SMR) is a method that can be used for producing hydrogen from natural gas. This is achieved in a processing device called a reformer which reacts steam at high temperature with the gas. SMR uses the following endothermic reaction:</p> $\text{CH}_4 + \text{H}_2\text{O} \rightleftharpoons \text{CO} + 3\text{H}_2.$ <p>The reaction is carried out at an activation energy of 206 kJ/mol and temperatures of 500-900 degrees Celsius [3]. In this SMR plant, a COGEN plant is running to export a relatively small fraction of the energy involved to the electricity grid. This plant involves the capture of CO2 from the pressure swing adsorption (PSA) tail gas using chemical absorption (using methyldiethanolamine - MDEA). This can achieve a CO2 avoidance of 52%.</p>
TRL level 2020	<p>TRL 9</p> <p>Mature technology. No more cost developments are assumed.</p>

TECHNICAL DIMENSIONS

Capacity	Functional Unit		Value and Range		
	MW		300		
Potential	MW	NL	Unlimited		
Market share	%		-		
Capacity utilization factor			1		
Unit of Activity			PJ/year		
Technical lifetime (years)			25		
Full-load running hours per year			8,322		
Progress ratio			0.95		
Hourly profile			No		
Explanation	IEA (2017) reports 100,000 Nm3/h at 10.8 MJ/Nm3, this translates into a capacity of precisely 300 MW hydrogen energy output. The progress ratio is found in Thomas (2009).				

COSTS

Year of Euro	2015									
Investment costs per year	Euro per Functional Unit		Current			2030			2050	
	mIn. € / MW		0.98	-	1.16	0.98	-	1.16	0.98	-
Other costs per year	mIn. € / MW		-			-			-	
			Min	-	Max	Min	-	Max	Min	-
Fixed operational costs per year (excl. fuel costs)	mIn. € / MW		0.03			0.03			0.03	
			0.03	-	0.07	0.03	-	0.07	0.03	-
Variable costs per year	mIn. € / MW		248,069			248,069			248,069	
			248,069	-	248,069	248,069	-	248,069	248,069	-
Costs explanation	<p>The data from NTNU (2016) is based on a different size plant, and the numbers in this factsheet are scaled to represent the same size plant as in IEA (2017). All costs exclude fuel costs and values are based on low heating value (LHV). Costs for CO2 capture are included. Sinnott (2009) finds a higher (per kg of hydrogen output) value for investment costs, which can in part be explained by the use of data for a smaller size plant. Conventional plants (such as SMR) benefit from economy of scale, therefore a scale-up factor of 0.8 can be used (Sinnott et al., 2009) when estimating the cost of a larger scale plant. Due to lack of data, there is an implicit assumption that the same scaling factor can be applied to this plant, including its carbon capture and storage (CCS) component.</p> <p>In these figures, the OPEX costs amount to 3.6 % of the CAPEX costs. Variable costs included are raw water make-up, catalysts and chemicals. Cost developments are taken relative to base year, and are found in Vita (2018).</p>									

ENERGY IN- AND OUTPUTS

Energy carriers (per unit of main output)	Energy carrier	Unit	Current			2030			2050		
	Main output:			-1.00			-1.00			-1.00	
Hydrogen		PJ	-1.00	-	-1.00	-1.00	-	-1.00	-1.00	-	-1.00
Electricity		PJ	-0.03			-0.03			-0.03		
			-0.03	-	0.00	-0.03	-	0.00	-0.03	-	0.00
Natural gas resource (gas fields)		PJ	1.48			1.48			1.48		
			1.04	-	1.48	1.04	-	1.48	1.04	-	1.48
		PJ	-			-			-		
			Min	-	Max	Min	-	Max	Min	-	Max
Energy in- and Outputs explanation	<p>The production of hydrogen of 10^5 Nm3/h gives 8.99 PJ/y. The 0.95 factor is to account for active running hours per year. Other values are taken from IEA (2017) and NTNU (2016) and scaled accordingly.</p> <p>The NTNU study reports on an energy efficiency of 0.82, however based on their own reported values of in- and outlet, an energy efficiency of 0.96 is found. A plant with an average power of 300 MW (with 0.95 factor) gives 8.99 PJ/year, therefore all numbers are scaled by 8.99 to give a result per PJ. The 0.95 factor accounts for the capacity utilization rate.</p>										

EMISSIONS (Non-fuel/energy-related emissions or emissions reductions (e.g. CCS))											
Emissions	Substance	Unit	Current			2030			2050		
	CO2	Mton				-0.04			-0.04		
			-0.04	-	-0.04	-0.04	-	-0.04	-0.04	-	-0.04
			<i>Min</i>	-	<i>Max</i>	<i>Min</i>	-	<i>Max</i>	<i>Min</i>	-	<i>Max</i>
			<i>Min</i>	-	<i>Max</i>	<i>Min</i>	-	<i>Max</i>	<i>Min</i>	-	<i>Max</i>
Emissions explanation											
			<i>Min</i>	-	<i>Max</i>	<i>Min</i>	-	<i>Max</i>	<i>Min</i>	-	<i>Max</i>
			<i>Min</i>	-	<i>Max</i>	<i>Min</i>	-	<i>Max</i>	<i>Min</i>	-	<i>Max</i>
IEA (2017) reports 0.8091 kg CO2/Nm3 hydrogen for the case without carbon capture and storage (CCS). This gives 0.675 Mton/year. In the OPERA model from ECN part of TNO (2018), these emissions are calculated from the fuel input. Therefore, for the purpose of this factsheet, all carbon emissions that are avoided due to CCS are specified as negative. With CCS, the number is extrapolated from that with IEA (2017) data. A plant with an average power of 300 MW (with 0.95 factor) gives 8.99 PJ/year, therefore all numbers are scaled by 8.99 to give a result per PJ. The 0.95 factor accounts for the capacity utilization rate.											
REFERENCES AND SOURCES											
IEA (2017). Techno-Economic Evaluation of SMR Based Standalone (Merchant) Hydrogen Plant with CCS. Accessed through https://ieaghg.org/exco_docs/2017-02.pdf											
Jakobsen, D., & Åtland, V. (2016). Concepts for large scale hydrogen production. Thesis, NTNU.											
Voldsund, M., Jordal, K., & Anantharaman, R. (2016). Hydrogen production with CO2 capture. International Journal of Hydrogen Energy, 41(9), 4969-4992.											
Expert opinion, Jacob Moulijn											
Sinnott, R. K., & Towler, G. (2009). Chemical engineering design: SI Edition. Elsevier.											
T. Ramsden, D. Steward and J. Zuboy, "Analyzing the Levelized cost of Centralized and Distributed Hydrogen Production Using the H2A production Model, Version 2," National Renewable Energy Laboratory, Virginia, 2009											
IEA, "Technology Roadmap - Hydrogen and Fuel Cells," OECD/IEA, 2015.											
Whitesides, Randall W. "Process equipment cost estimating by ratio and proportion." Course notes, PDH Course G 127 (2005).											
Vita et al (2018). Sectoral integration- long-term perspective in the EU Energy System. ASSET											
Thomas (2009). Low-Cost Hydrogen Distributed Production System Development											